

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION  
International Bureau




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<p>(51) International Patent Classification 5 : <b>G03G 15/16</b></p>	<p><b>A1</b></p>	<p>(11) International Publication Number: <b>WO 90/04216</b> (43) International Publication Date: <b>19 April 1990 (19.04.90)</b></p>
<p>(21) International Application Number: <b>PCT/NL89/00073</b> (22) International Filing Date: <b>3 October 1989 (03.10.89)</b> (30) Priority data: <b>8823256.6</b>      <b>4 October 1988 (04.10.88)</b>      <b>GB</b> (71) Applicant: <b>SPECTRUM SCIENCES B.V. [NL/NL];</b> <b>Zijdweg 6, NL-2244 BG Wassenaar (NL).</b> (72) Inventors: <b>LANDA, Benzion ; 10010-119 Street, Edmon-</b> <b>ton, Alberta T5J 0W0 (CA). LIOR, Ishaiau ; 21, Bilu</b> <b>Street, Ness Ziona (IL). PINHAS, Hanna ; 29, Shprin-</b> <b>zak Street, 58 100 Holon (IL).</b> (74) Agents: <b>DE BRUIJN, Leendert, C. et al.; Nederlandsch</b> <b>Octrooibureau, Scheveningseweg 82, P.O. Box 29720,</b> <b>NL-2502 LS The Hague (NL).</b></p>		<p>(81) Designated States: <b>AT (European patent), BE (European patent), CH (European patent), DE (European patent), FR (European patent), GB (European patent), IT (European patent), JP, LU (European patent), NL (European patent), SE (European patent).</b>  <b>Published</b> <i>With international search report.</i> <i>With amended claims.</i></p>

(54) Title: METHOD AND APPARATUS FOR IMAGING USING AN INTERMEDIATE TRANSFER MEMBER

(57) Abstract

Method an apparatus for transfer of a liquid toner image, containing carrier liquid and toner particles which solvate the carrier liquid at a solvation temperature above room temperature, from an image bearing surface to a substrate, the apparatus including an intermediate transfer member positioned in operative association with the image bearing surface, transferring the image from the image bearing surface onto the intermediate transfer member, and heating the image on the intermediate transfer member to a temperature above the solvation temperature, below the melting point of the toner particles and below the boiling point of the carrier liquid prior to transfer of the image to the substrate so as to cause the image to adhere to the substrate. There is also provided imaging apparatus including a flexible substrate, apparatus for tensioning the flexible substrate in at least two directions and apparatus for bringing the tensioned flexible substrate into image transfer engagement with an image bearing surface. A method of imaging using the apparatus is also described.



**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	ES	Spain	MG	Madagascar
AU	Australia	FI	Finland	ML	Mali
BB	Barbados	FR	France	MR	Mauritania
BE	Belgium	GA	Gabon	MW	Malawi
BF	Burkina Faso	GB	United Kingdom	NL	Netherlands
BG	Bulgaria	HU	Hungary	NO	Norway
BJ	Benin	IT	Italy	RO	Romania
BR	Brazil	JP	Japan	SD	Sudan
CA	Canada	KP	Democratic People's Republic of Korea	SE	Sweden
CF	Central African Republic	KR	Republic of Korea	SN	Senegal
CG	Congo	LI	Liechtenstein	SU	Soviet Union
CH	Switzerland	LK	Sri Lanka	TD	Chad
CM	Cameroon	LU	Luxembourg	TG	Togo
DE	Germany, Federal Republic of	MC	Monaco	US	United States of America
DK	Denmark				

METHOD AND APPARATUS FOR IMAGING USING AN  
INTERMEDIATE TRANSFER MEMBER

FIELD OF THE INVENTION

The present invention relates generally to imaging apparatus  
5 and techniques and more particularly to apparatus and techniques  
for transfer of images from an image-bearing surface to a  
substrate via an intermediate transfer medium.

BACKGROUND OF THE INVENTION

Various techniques for electrostatic image transfer are  
10 known in the patent literature. U.S. Patent 4,684,238 describes  
intermediate transfer apparatus in which a plurality of liquid  
images, which include a liquid carrier having toner particles  
dispersed therein, are attracted from a photoconductive member  
to an intermediate belt. Liquid carrier is removed from the  
15 intermediate belt by vacuum apparatus and the toner particles are  
compacted on the intermediate belt in image configuration.  
Thereafter, the toner particles are transferred from the  
intermediate belt to the copy sheet in image configuration by  
electrostatic attraction.

20 U.S. Patent 4,690,539 shows a system similar to that shown  
in U.S. Patent 4,684,238 which is suitable for multi-color  
multiple-pass electrophoretic image transfer.

- 2 -

In U.S. Patents 3,318,212 and 3,893,761 there are described methods and devices in which a powder image being transported on a resiliently deformable intermediate support surface is softened and thus rendered sticky while present on that surface and then is transferred and fixed onto a paper receiving support under the influence of pressure.

U.S. Patent 4,015,027 describes an electrophotographic toner transfer and fusing method wherein a heated roller or belt is employed for pressure transfer of dry toner images from an intermediate transfer medium onto paper. At column 11, line 29 - column 12 line 38 there appears a detailed discussion of heating of images upon transfer thereof as proposed therein and as taught in the prior art including specifically U.S. Patent 3,591,276 to Byrne.

Reference is made to Figs. 5A - 5C, 6A - 6C, 7A and 7C of U.S. Patent 4,015,027. It is seen that in nearly all cases described, the toner is heated to at least its melting point during the transfer stage. In a technique proposed in U.S. Patent 4,015,027 and exemplified by Fig. 6(a), the toner is heated to at least its melting point prior to the transfer zone. In the transfer zone, the toner cools below its melting point during transfer and fusion.

A belt construction characterized in that it has a very low heat capacitance and a thickness of between 15 and about 200

- 3 -

microns is proposed in U.S. Patent 4,015,027. In one embodiment the belt comprises a 50 micron layer of aluminized Kapton having a 25 micron coating of silicon rubber. Another embodiment employs a 12.5 micron layer of stainless steel instead of the Kapton together with a silicon rubber coating. A reflecting layer is incorporated in the belt to reduce heating thereof.

U.S. Patent 4,796,048 describes a system for transferring a liquid toner image from a photoconductive member to an intermediate transfer member for subsequent transfer to a copy sheet. In several of the examples the liquid toner image is heated to remove solvent associated with the toner image. The toner particles are melted to thermally offset the image to the copy sheet.

U. S. Patent 4,708,460 describes a system for transferring a liquid toner image from a photoconductive member to an intermediate transfer member for subsequent transfer to a copy sheet. The liquid toner image is heated by radiant heat on the intermediate transfer member to vaporize some of the liquid carrier and to partially melt the toner particles, decreasing their viscosity. During transfer to the final substrate heat substantially vaporizes the remainder of the liquid carrier from the image and fuses the image to the copy sheet.

SUMMARY OF THE INVENTION

The present invention seeks to provide improved imaging apparatus.

5 There is therefor provided apparatus for transfer of a liquid toner image (containing carrier liquid and toner particles which solvate the carrier liquid at a solvation temperature above room temperature) from an image bearing surface to a substrate, the apparatus comprising: an intermediate transfer member arranged in operative association with the image bearing surface, 10 first transfer means operative for transferring the image from the image bearing surface onto the intermediate transfer member, and heating apparatus operative for heating the image on the intermediate transfer member to a temperature above the solvation temperature, below the melting point of the toner particles and 15 below the boiling point of the carrier liquid prior to transfer of the image to the substrate so as to cause the image to adhere to the substrate.

In accordance with a preferred embodiment of the invention the apparatus also comprises second transfer means operative for 20 transferring the heated image from the intermediate transfer member to a substrate, the second transfer means being operative for cooling the intermediate transfer member sufficiently such that the adhesion of the image thereto is less than the cohesion of the image. In a preferred embodiment of the invention the

second transfer means in conjunction with the substrate is operative to cool the image sufficiently such that the adhesion of the image to the intermediate transfer member is less than the cohesion of the image.

5       The first transfer means includes, in a preferred embodiment of the invention, apparatus for transferring multiple images from the image bearing surface onto the intermediate transfer member.

      In a preferred embodiment of the invention the toner particles in the liquid toner image are pigmented.

10       Further in a preferred embodiment of the invention the heating apparatus is operative to heat the image such that the image remains at a temperature above the solvation temperature until contact of the image with the substrate.

15       Further in accordance with a preferred embodiment of the invention, the intermediate transfer member comprises a thin walled cylinder preferably with a thickness of less than 125 microns. In alternative preferred embodiments the wall thickness may be less than 50, less than 30 or less than 7 microns. In a preferred embodiment of the invention the thin walled cylinder includes metallic material. In a preferred embodiment the thin  
20       walled cylinder comprises a layer of polymer material and a thin release layer.

      In a preferred embodiment of the invention, the intermediate

transfer member includes a relatively heat conductive inner layer and a relatively heat insulative outer layer.

In a preferred embodiment of the invention the intermediate transfer member has a low effective heat capacity such that the surface temperature of the intermediate transfer member is substantially reduced during transfer of an image therefrom onto substrate.

There is additionally provided a method for transfer of a liquid toner image (containing carrier liquid and toner particles which solvate the carrier liquid at a solvation temperature above room temperature) from an image bearing surface to a substrate, including the steps of: transferring the image from the image bearing surface onto an intermediate transfer member, and heating the image on the intermediate transfer member to a temperature above the solvation temperature, below the melting point of the toner particles and below the boiling point of said carrier liquid prior to transfer of the image to the substrate so as to cause the image to adhere to the substrate.

The method includes, in a preferred embodiment of the invention, the step of cooling the intermediate transfer member sufficiently such that the adhesion of the image thereto is less than the cohesion of the image. In a preferred embodiment of the invention the image is cooled sufficiently such that the adhesion of the image to the intermediate transfer member is less than the



cohesion of the image.

In a preferred embodiment of the invention the step of transferring the image from the image bearing surface is repeated a plurality of times, each transfer corresponding to an image of a different color.

The method preferably includes the step of transferring the heated image from the intermediate transfer member to the substrate, wherein the step of transferring the image from the intermediate transfer member onto the substrate is operative to cool the image to below the solvation temperature.

There is also provided in accordance with a further preferred embodiment of the present invention apparatus for transfer of an image from an image bearing surface onto a substrate including an intermediate transfer member positioned in operative association with the image bearing surface, means for transferring an image from the image bearing surface onto the intermediate transfer member, and means for transferring the image from the intermediate transfer member onto a substrate and being operative for heating the intermediate transfer member and the image so as to cause the image to adhere to the substrate and for cooling the intermediate transfer member sufficiently such that the adhesion of the image thereto is less than the cohesion of the image.

There is also provided in accordance with yet a further

- 8 -

preferred embodiment of the present invention apparatus for transfer of multiple images from an image bearing surface onto a substrate including an intermediate transfer member positioned in operative association with the image bearing surface, means for transferring multiple images from the image bearing surface onto the intermediate transfer member, and means for transferring the multiple images from the intermediate transfer member onto a substrate and being operative for heating the intermediate transfer member and the image so as to cause the image to adhere to the substrate and for cooling the intermediate transfer member sufficiently such that the adhesion of the image thereto is less than the cohesion of the image.

There is further provided in accordance with an additional preferred embodiment of the present invention apparatus for transfer of an image from an image bearing surface onto a substrate including an intermediate transfer member positioned in operative association with the image bearing surface, means for transferring an image from the image bearing surface onto the intermediate transfer member, and means for transferring the image from the intermediate transfer member onto a substrate and wherein the intermediate transfer member includes a thin walled cylinder of thickness less than 125 microns.

There is also provided in accordance with yet a further embodiment of the present invention apparatus for transfer of multiple images from an image bearing surface onto a substrate

including an intermediate transfer member positioned in operative association with the image bearing surface, means for transferring multiple images from the image bearing surface onto the intermediate transfer member, and means for transferring the  
5 multiple images from the intermediate transfer member onto a substrate and wherein the intermediate transfer member includes a thin walled cylinder of thickness less than 125 microns.

There is additionally provided in accordance with yet a further embodiment of the present invention apparatus for  
10 transfer of an image from an image bearing surface onto a substrate including an intermediate transfer member positioned in operative association with the image bearing surface; means for transferring an image from the image bearing surface onto the  
15 intermediate transfer member, and means for transferring the image from the intermediate transfer member onto a substrate and wherein the intermediate transfer member includes a relatively heat conductive inner layer and a relatively heat insulative outer layer.

There is also provided in accordance with an additional  
20 embodiment of the present invention apparatus for transfer of multiple images from an image bearing surface onto a substrate including an intermediate transfer member positioned in operative association with the image bearing surface, means for  
25 transferring multiple images from the image bearing surface onto the intermediate transfer member, and means for transferring the multiple images from the intermediate transfer member onto a

- 10 -

substrate and wherein the intermediate transfer member includes a relatively heat conductive inner layer and a relatively heat insulative outer layer.

5 There is further provided in accordance with a further preferred embodiment of the present invention an intermediate transfer member for transfer of an image from an image bearing surface onto a substrate and including a thin walled cylinder having a thickness less than 125 microns.

10 There is also provided in accordance with an additional preferred embodiment of the present invention an intermediate transfer member for transfer of an image from an image bearing surface onto a substrate and including a relatively heat conductive inner layer and a relatively heat insulative outer layer.

15 There is additionally provided in accordance with yet a further embodiment of the present invention a method for transfer of an image from an image bearing surface onto a substrate including the steps of positioning an intermediate transfer member in operative association with the image bearing  
20 surface, transferring an image from the image bearing surface onto the intermediate transfer member, and transferring the image from the intermediate transfer member onto a substrate and including the steps of heating the intermediate transfer member and the image so as to cause the image to adhere to the substrate  
25 and cooling the intermediate transfer member sufficiently such

- 11 -

that the adhesion of the image thereto is less than the cohesion of the image.

There is additionally provided in accordance with a further preferred embodiment of the present invention a method for transfer of multiple images from an image bearing surface onto a substrate including the steps of positioning an intermediate transfer member in operative association with the image bearing surface, transferring multiple images from the image bearing surface onto the intermediate transfer member, and transferring the multiple images from the intermediate transfer member onto a substrate including the steps of heating the intermediate transfer member and the image so as to cause the image to adhere to the substrate and cooling the intermediate transfer member sufficiently such that the adhesion of the image thereto is less than the cohesion of the image.

BRIEF DESCRIPTION OF THE DRAWINGS

The present invention will be understood and appreciated more fully from the following detailed description taken in conjunction with the drawings in which:

5        Fig. 1 is a generalized schematic sectional illustration of imaging apparatus constructed and operative in accordance with a preferred embodiment of the present invention;

      Figs. 2A, 2B and 2C are illustrations of transfer of an image from an intermediate transfer element onto a substrate;

10       Fig. 3 is a generalized illustration of viscosity as a function of temperature;

      Fig. 4A is a side sectional illustration of a heated thin-walled intermediate transfer element constructed and operative in accordance with a preferred embodiment of the present invention;

15       Fig. 4B is a sectional illustration taken along the lines IV - IV of Fig. 4A;

      Fig. 5A is a side sectional illustration of a heated thin-walled intermediate transfer element constructed and operative in accordance with an alternative embodiment of the present invention;

20

      Fig. 5B is a sectional illustration taken along the lines V

- V of Fig. 5A;

Fig. 6A is a side sectional illustration of a heated thin-walled intermediate transfer element constructed and operative in accordance with a further alternative embodiment of the present invention;

Fig. 6B is a sectional illustration taken along the lines VI - VI of Fig. 6A;

Fig. 7A is a side sectional illustration of a heated thin-walled intermediate transfer element constructed and operative in accordance with yet another embodiment of the present invention;

Fig. 7B is a sectional illustration taken along the lines VII - VII of Fig. 7A;

Fig. 8 is a sectional illustration of a partially heated intermediate transfer element; and

Fig. 9 is a graphical illustration of the temperature variation on a low thermal mass intermediate transfer element in an arrangement such as that illustrated in Fig. 8.

- 14 -

DETAILED DESCRIPTION OF THE INVENTION

Referring to Fig. 1 there is shown electrostatographic imaging apparatus in which the present invention may be employed and employing a liquid image forming composition. In a general sense, the imaging apparatus may comprise an electrostatographic printing machine or alternatively any other suitable type of imaging apparatus. Examples of systems in which the present invention may be employed include electrophotography, electrography, ionography, xero-printing, gravure-like printing and electrostatic printing.

For convenience, the description which follows is presented in the context of an electrophotographic system employing liquid toner, but without limiting the applicability of the present invention.

A metal drum 10, having formed thereon a photoconductive surface 12, is mounted on a shaft 14. Drum 10 is driven in the direction of arrow 16 such that the photoconductive surface 12 moves past a corona discharge device 18 adapted to charge the photoconductive surface 12. An image to be reproduced is focused by a lens 20 upon the photoconductive surface 12. The areas of the photoconductive surface 12 struck by light conduct the charge, or a portion thereof, to ground, thus forming an electrostatic latent image.



- 15 -

Developer liquid containing pigmented particles is circulated from any suitable source into a gap 22 defined between a development electrode 24 and the photoconductive surface 12. The development electrode 24 may be appropriately  
5 biased as known to the art, to assist in toning the electrostatic latent image as it passes into contact with the developer liquid.

Charged toner particles suspended in a carrier liquid, both of which form part of the developer liquid, travel by  
10 electrophoresis to the electrostatic latent image.

Excess liquid is removed from the developed image by metering apparatus which may incorporate a reverse roller indicated generally at reference numeral 30.

Transfer of the image to a carrier sheet 40, such as paper, supported by a platen roller 42, is effected by an intermediate  
15 transfer assembly 50 which is a subject of the present invention.

The transfer assembly 50 comprises an intermediate transfer element 52, typically in the form of a cylindrical roller. The intermediate transfer element 52 is preferably an intermediate  
20 transfer element of the type illustrated in any of Figs. 4A - 7B.

Transfer of the image from the photoconductive surface 12 to the intermediate transfer element 52 may take place in accordance with any suitable technique known in the prior art. Examples of

- 16 -

suitable techniques are electrostatic transfer, heat transfer, pressure transfer, electrophoretic transfer and combinations thereof. A preferred transfer method is electrophoretic transfer.

After the image is transferred from the photoconductive surface 12 to the intermediate transfer element 52, continued rotation of the photoconductive surface 12 in the direction of arrow 16 brings the surface past a conventional cleaning station 32 and a flood exposure light 34, for removing vestiges of prior images.

In accordance with a preferred embodiment of the invention the liquid toner image is heated on the intermediate transfer member 52. Heating of the image enhances its cohesiveness and renders it tacky, so as to enhance its adhesion to the substrate 40.

Although the invention is not limited in its application to specific materials or to liquid toner, the following specific example is provided for the purposes of illustration. There is employed a toner which is prepared in the following manner:

1000g. Elvax II 5550 resin (DuPont) and 500g. Isopar L were mixed in a Ross double planetary mixer for one hour at 90 degrees C, then for a further hour after addition of 250g. Mogul L carbon black (Cabot) which had been wetted by 500g. Isopar L, and finally for another hour after addition of 2000g. Isopar L

- 17 -

preheated to 110 degrees C. Stirring was continued in the absence of heating until the temperature reached 40 degrees C. 3050 grams of the resultant mixture was milled in a Sweco M-18 vibratory mill (containing 0.5" alumina cylinders) with 4000g. Isopar L for 20 hours at 34 degrees C; the average particle size of the product was 2.3 microns. The product was diluted to a 1.5% solids content with Isopar L and between 5 - 20 ml of 10% Lecithin charge director was added to the diluted dispersion.

The image 60 located on the intermediate transfer element 52 is heated, by means which will be described hereinbelow, to a temperature which produces desired tackiness of the image. Then the heated image establishes contact with the substrate 40 as shown in Fig. 2A.

According to a preferred embodiment of the present invention, wherein a toner of the type described in detail on the preceding page, a toner of the type described in U.S. Patent 4,794,651, the contents of which are hereby incorporated herein by reference, or any other liquid toner which solvates at a temperature below its melting point is used, the image 60 is heated to a temperature below the melting point of the dry resin but above the temperature at which the resin swells or begins to solvate with the carrier liquid and becomes tacky, and below the boiling point of the carrier liquid. Alternatively a liquid toner which does not solvate at a temperature below the melting point of the pigmented solid particles therein may be employed. In such

- 18 -

a case, heating of the image to a temperature as high as the melting point of the pigmented solid particles therein is required.

5 It is a particular feature of the present invention that while the image 60 is in contact with both the element 52 and the substrate 40, as shown in Fig. 2B, for a duration which will be termed the "transfer duration", the heat transfer to the image from the element 52 and from the image to the substrate 40 is preferably such that the image is cooled, so as to increase its  
10 viscosity, while at least maintaining and preferably increasing its cohesiveness. In this way, complete or nearly complete transfer of the image from the intermediate transfer element 52 to the substrate is realized. Fig. 2C illustrates the complete or nearly complete transfer of the image to the substrate 40.

15 If the specific material discussed above is employed as an example, the following exemplary temperatures may be used. The image 60 and member 52 are initially heated to a temperature T 1 of 105 degrees C, which is below the melting point of the resin but above the solvation temperature. During the "transfer  
20 duration" the temperature of the image/paper interface is reduced to a temperature T 2 of 85 degrees C, at which the viscosity is increased over that at the higher temperature.

Reference is made in this context to Fig. 3 which is an illustration, not necessarily to scale, of the dependence of

- 19 -

viscosity of an image on temperature. It is seen that the reduction of temperature from T 1 to T 2 provides a corresponding significant rise in viscosity.

5 It will be appreciated that the image is initially heated to a temperature at which it solvates, so that it will adhere well to the substrate. The image is then cooled, increasing its viscosity and thus increasing its cohesiveness. The adhesion of the image to the substrate is greater than its adhesion to the release coated intermediate transfer member, and the increased cohesion of the image preserves the integrity of the transferred image, providing substantially complete transfer of the image to the substrate.

15 Reference is now made to Figs. 4A - 7B which illustrate four alternative embodiments of intermediate transfer elements constructed and operative in accordance with a preferred embodiment of the invention.

20 According to a preferred embodiment of the invention, the intermediate transfer element comprises a thin-walled roller 70. Roller 70 preferably is formed of two rigid end portions 72 and 74 and a thin cylindrical layer 76 typically coated with a release layer 78. Typical materials and thicknesses are as follows:

Layer 76: metalized polyester

Thickness: 25 microns

- 20 -

Release layer 78: Teflon (DuPont)

Thickness: 5 microns

According to an alternative embodiment of the invention, the layer 76 may be a 5 micron thick film of nickel alloy, such as a nickel cobalt or nickel chromium alloy and the release layer may be a 2 micron thick layer of Teflon.

According to a further alternative embodiment of the invention, Kapton polyimide film (DuPont) may be employed instead of polyester.

According to a further alternative embodiment of the invention the release layer may be a thin layer of silicone rubber.

In accordance with a preferred embodiment of the invention, the thin cylindrical layer 76 is axially tensioned, as by a spring arrangement 80, sufficient to eliminate most surface irregularities. For the above-described example employing metalized polyester, for a cylinder of diameter 50 mm, a suitable tension is 10 Kg.

Further in accordance with a preferred embodiment of the invention, enhanced rigidity and surface uniformity of the thin-walled cylinder 70 is provided by pneumatically pressurizing the interior of the cylinder, by any suitable pressurized gas. A valve 82 may be provided for this purpose.

- 21 -

In accordance with a preferred embodiment of the present invention, the thin-walled cylinder 70 is heated by the passage of electrical current along layer 76 via conductors 84 and 86, which establish an electrical circuit via end portions 72 and 74. In this case layer 76 must either be or include a layer which is an electrical conductor of suitable characteristics.

In the above stated example, the electrical power required to provide desired heating of the intermediate transfer element 70 is relatively low.

Reference is now made to Figs. 5A and 5B which illustrate an alternative embodiment of a heated intermediate transfer element wherein heating is provided by radiation. Here a heating lamp 90 is disposed interior of a radiation transmissive tube 92, such as a quartz tube. Disposed in generally coaxial surrounding relationship with quartz tube 92 and supported on annular end supports 94 is an intermediate transfer layer 96 having formed thereon a release layer 98.

According to one embodiment of the invention, layers 96 and 98 may be identical to layers 76 and 78 in the embodiment of Figs. 4A and 4B. In such a case tensioning apparatus of the type illustrated in Fig. 4A may be employed. Alternatively layers 96 and 98 which are more massive and thus more rigid than layers 76 and 78 may be employed. In such a case the release layer 98 is provided with sufficient thermal insulation capacity to limit the

- 22 -

amount of thermal conduction therethrough so that during transfer of the image to the substrate 40, the image may be cooled as described above in connection with the thin-walled intermediate transfer element. Suitable materials and thicknesses for the non-  
5 thin-walled intermediate transfer element are as follows:

Layer 96: Aluminum

Thickness: 5 mm

Layer 98: Silicone rubber

Thickness: 2 mm

10 Reference is now made to Figs. 6A and 6B, which illustrate an alternative arrangement of heated intermediate transfer roller. The roller 100 may be either of the thin-walled type or of the non-thin-walled type described above. Heating of the roller 100 is provided externally of the roller by a heating  
15 station 102. In the illustrated embodiment, the heating station 102 employs radiant heaters, which heat the roller by radiation. Alternatively the heating station 102 may heat the roller 100 by conduction through direct contact with the roller.

20 Reference is now made to Figs. 7A and 7B, which illustrate a further alternative of heated intermediate roller arrangement. Here, once again, a roller 110 may be either thin-walled or non-thin-walled. Heating of the roller 110 is provided by an internal radiant heater assembly 112 which is mounted internally of roller 110. Radiant heater 112 comprises an elongate radiative heat



- 23 -

source 114 which is associated with a reflector 116, which prevents direct radiation from source 114 from reaching the area at which the image is transferred from the roller 110 to substrate 40 (Fig. 1), thus providing differential heating of roller 110 and permitting cooling of the image during transfer as described hereinabove.

A suitable weight 118 may be mounted onto the reflector 116 so that when the reflector 116 and weight 118 are pivotably mounted with respect to the roller, they will retain the orientation illustrated, notwithstanding rotation of the roller 110.

It is a particular feature of the present invention that there is provided an intermediate transfer member including a thin surface which supports the image during transfer, the thin surface having an effective heat capacity per unit area which is less than that of the substrate.

The thin surface may be a cylindrical surface or alternatively an endless belt or any other configuration. Normally, due to its thinness, the thermal conductivity along the surface is sufficiently small such that the thermal mass of the supports, such as end rollers for a cylindrical surface like that shown in the drawings, may be disregarded.

It is a particular feature of the present invention that the effective thermal mass of the intermediate transfer element, as

- 24 -

sensed by an object coming into contact with its outer surface is relatively small. This may be achieved either by the use of a thin-walled roller as described hereinabove, whose inherent thermal mass is limited, or alternatively by the use of a roller, other than a thin-walled roller, but having an outer layer which is a sufficiently good thermal insulator such that the heat transfer characteristics thereof are as required. Such a structure has been described above.

The advantages of the use of an intermediate transfer element having a low effective thermal mass are summarized below:

- a. enabling the image at the transfer region of the intermediate transfer element to be cooled during transfer, as has already been described;
- b. enabling rapid cooling of the intermediate transfer element and thus eliminating the need for separating it from the photoconductor when operation is interrupted;
- c. limiting the amount of thermal energy passed to the paper and thus reducing energy consumption and limiting paper deformation;
- d. enabling differential heating of the intermediate transfer element such that it cools down from the onset of transfer to the onset of photoconductor contact to a temperature at which contact with the photoconductor will not cause

- 25 -

photoconductor damage.

Reference is made in this context to Fig. 8 which illustrates a variation of the apparatus of Figs. 7A and 7B, using identical reference numerals where appropriate, wherein a reflector is oriented so as to prevent direct radiation heating of the roller from the transfer stage through the photoconductor contact stage. In such a situation the approximate roller temperature at various locations therealong is as shown in Fig. 9.

It can be seen from a consideration of Figs. 8 and 9 that the intermediate transfer member gives up a measured quantity of heat to the substrate during image transfer thereto (between locations B and C) and remains at a relatively low temperature, i.e. below about 85 degrees centigrade, until it contacts the photoconductive surface 12, at which point it gives up further heat very quickly to the photoconductive surface 12 (between locations D and E). The photoconductive surface does not heat up appreciably in view of its relatively large thermal mass. The intermediate transfer member remains at generally the same temperature until it is exposed to radiation heating (at location 0) and is heated gradually until it reaches a steady state temperature (at location A) just before transfer contact with the substrate (at location B).

This development takes place at a first temperature T ;  
1

- 26 -

transfer of the image to the intermediate transfer member takes place at an image temperature  $T_2$ , higher than  $T_1$  and final transfer from the intermediate transfer member to the substrate takes place at a temperature  $T_3$  higher than temperature  $T_2$ .

5        It is a particular feature of the present invention that the temperature of the intermediate transfer member when it is in propinquity to the photoconductive surface 12 is sufficiently low as to preclude damage to the photoconductive surface 12, even during prolonged contact or propinquity, as when neither of the  
10        surfaces is rotating. Accordingly prior art mechanisms for separating the intermediate transfer member from the photoconductive surface 12 when the apparatus is not in operation are not required.

15        It will be appreciated by persons skilled in the art that the present invention is not limited by what has been particularly shown and described hereinabove. Rather the scope of the present invention is defined only by the claims which follow:

## C L A I M S

1. Apparatus for transfer of a liquid toner image, containing carrier liquid and toner particles which solvate said carrier liquid at a solvation temperature above room temperature, from an image bearing surface to a substrate, the apparatus comprising:
  - an intermediate transfer member arranged in operative association with said image bearing surface;
  - first transfer means operative for transferring said image from said image bearing surface onto said intermediate transfer member; and
  - heating means operative for heating said image on said intermediate transfer member to a temperature above said solvation temperature, below the melting point of the toner particles and below the boiling point of said carrier liquid prior to transfer of the image to said substrate so as to cause the image to adhere to said substrate.
2. Apparatus according to claim 1 and comprising second transfer means operative for transferring said heated image from said intermediate transfer member to said substrate, said second transfer means being operative for cooling said intermediate transfer member sufficiently such that the adhesion of said image thereto is less than the cohesion of said image.
3. Apparatus according to claim 1 wherein said first transfer

- 28 -

means includes means for transferring multiple images from said image bearing surface onto said intermediate transfer member.

4. Apparatus according to claim 1 wherein said toner particles in said liquid toner image are pigmented.
- 5 5. Apparatus according to claim 1 wherein said heating means is operative to heat said image such that said image remains at a temperature above said solvation temperature until contact of said image with said substrate.
- 10 6. Apparatus according to claim 1 wherein said second transfer means in conjunction with said substrate is operative to cool said image sufficiently such that the adhesion of the image to said intermediate transfer member is less than the cohesion of said image.
- 15 7. Apparatus according to claim 1 wherein said intermediate transfer member comprises a thin walled cylinder.
8. Apparatus according to claim 7 wherein said thin walled cylinder has a thickness less than 125 microns.
- 20 9. Apparatus according to claim 7 wherein said thin walled cylinder has a thickness less than about 50 microns.
10. Apparatus according to claim 7 wherein said thin walled cylinder has a thickness less than about 30 microns.

- 29 -

11. Apparatus according to claim 15 wherein said thin walled cylinder comprises a layer of polymer material and a thin release layer.
12. Apparatus according to claim 7 wherein said thin walled cylinder has a thickness less than about 7 microns.
13. Apparatus according to claim 7 wherein said thin walled cylinder comprises a metallic material.
14. Apparatus according to claim 1 wherein said intermediate transfer member comprises a relatively heat conductive inner layer and a relatively heat insulative outer layer.
15. Apparatus according to claim 1 and wherein said intermediate transfer member has a low effective heat capacity such that the surface temperature of said intermediate transfer member is substantially reduced during transfer of said image therefrom onto said substrate.
16. A method for transfer of a liquid toner image, containing carrier liquid and toner particles which solvate said carrier liquid at a solvation temperature above room temperature, from an image bearing surface to a substrate, comprising the steps of:
- transferring said image from said image bearing surface onto an intermediate transfer member; and
- heating said image on said intermediate transfer member to a

- 30 -

temperature above said solvation temperature, below the melting point of the toner particles and below the boiling point of said carrier liquid prior to transfer of said image to said substrate so as to cause said image to adhere to said substrate.

- 5 17. The method of claim 16 and including the step of cooling said intermediate transfer member sufficiently such that the adhesion of said image thereto is less than the cohesion of the image.
- 10 18. The method of claim 16 and including the step of cooling said image sufficiently such that the adhesion of said image to said intermediate transfer member is less than the cohesion of said image.
- 15 19. The method of claim 16 and wherein the step of transferring said image from said image bearing surface is repeated a plurality of times, each transfer corresponding to an image of a different color.
- 20 20. A method according to claim 16 and including the step of transferring said heated image from said intermediate transfer member to said substrate, wherein said step of transferring the image from the intermediate transfer member onto said substrate is operative to cool said image to below said solvation temperature.
21. Apparatus for transfer of an image from an image bearing



- 31 -

surface onto a substrate comprising:

an intermediate transfer member positioned in operative association with the image bearing surface;

5 means for transferring an image from the image bearing surface onto the intermediate transfer member; and

means for transferring the image from the intermediate transfer member onto a substrate and being operative for heating the intermediate transfer member and the image so as to cause the image to adhere to the substrate and for cooling the intermediate transfer member sufficiently such that the adhesion of the image thereto is less than the cohesion of the image.

10

22. Apparatus for transfer of multiple images from an image bearing surface onto a substrate comprising:

an intermediate transfer member positioned in operative association with the image bearing surface;

15

means for transferring multiple images from the image bearing surface onto the intermediate transfer member; and

means for transferring the multiple images from the intermediate transfer member onto a substrate and being operative for heating the intermediate transfer member and the image so as to cause the image to adhere to the substrate and for cooling the intermediate transfer member sufficiently such that the adhesion of the image thereto is less than the cohesion of the image.

20

23. Apparatus according to claim 21 or 22 wherein the image is a toner image and wherein said means for transferring the image from the intermediate transfer member to said substrate is operative to heat the toner image to a temperature below its melting point.  
5
24. Apparatus according to claim 21 or 22 wherein the image is a liquid toner image including particles and wherein said means for transferring the image from the intermediate transfer member to said substrate is operative to heat the liquid toner image to a temperature below the melting point of said particles.  
10
25. Apparatus according to claim 21 or 22 wherein the image is a liquid image including pigmented particles and wherein said means for transferring the image from the intermediate transfer member to said substrate is operative to heat the liquid image to a temperature below the melting point of said pigmented particles.  
15
26. Apparatus according to claim 21 or 22 wherein said means for transferring the image from the intermediate transfer means onto said substrate is operative to heat said image to a temperature at which it solvates.  
20
27. Apparatus according to claim 26 wherein said means for transferring the image from the intermediate transfer means onto

- 33 -

said substrate is operative to cool said image to below said solvation temperature.

28. Apparatus according to claim 21 or 22 wherein the image is a toner image and wherein said means for transferring the image from the intermediate transfer member to said substrate is operative to heat the toner image to a temperature above its melting point.

29. Apparatus according to claim 21 or 22 wherein the image is a liquid image including pigmented particles and wherein said means for transferring the image from the intermediate transfer member to said substrate is operative to heat the liquid image to a temperature above the melting point of said pigmented particles.

30. Apparatus according to claim 29 wherein said means for transferring the image from the intermediate transfer means onto said substrate is operative to cool said image to below said melting point.

31. Apparatus according to claim 21 or 22 wherein said intermediate transfer member comprises a thin walled cylinder.

32. Apparatus according to claim 31 wherein said thin walled cylinder has a thickness less than 125 microns.

- 34 -

33. Apparatus for transfer of an image from an image bearing surface onto a substrate comprising:

an intermediate transfer member positioned in operative association with the image bearing surface;

5 means for transferring an image from the image bearing surface onto the intermediate transfer member; and

means for transferring the image from the intermediate transfer member onto a substrate and wherein said intermediate transfer member comprises a thin walled cylinder of thickness  
10 less than 125 microns.

34. Apparatus for transfer of multiple images from an image bearing surface onto a substrate comprising:

an intermediate transfer member positioned in operative association with the image bearing surface;

15 means for transferring multiple images from the image bearing surface onto the intermediate transfer member; and

means for transferring the multiple images from the intermediate transfer member onto a substrate and wherein said intermediate transfer member comprises a thin walled cylinder of  
20 thickness less than 125 microns.

35. Apparatus according to claim 32, 33 or 34 wherein said thin walled cylinder has a thickness less than about 50 microns.

- 35 -

36. Apparatus according to claim 35 wherein said thin walled cylinder has a thickness less than about 30 microns.

37. Apparatus according to any of claims 32, 33 or 34 wherein said thin walled cylinder comprises a layer of polyester and a thin release layer.

38. Apparatus according to any of claims 32, 33 or 34 wherein said thin walled cylinder comprises a layer of Kapton and a thin release layer.

39. Apparatus according to claim 36 wherein said thin walled cylinder has a thickness less than about 7 microns.

40. Apparatus according to claim 36 wherein said thin walled cylinder comprises a metallic material.

41. Apparatus according to claim 40 wherein said thin walled cylinder comprises a layer of nickel alloy and a thin release layer.

42. Apparatus according to claim 36 and also comprising means for passing electrical current through said thin walled cylinder for producing direct resistance heating thereof.

- 36 -

43. Apparatus according to claim 35 wherein said intermediate transfer member also comprises means for axially tensioning said thin walled cylinder.
44. Apparatus according to claim 35 wherein said thin walled  
5 cylinder is a pneumatically pressurized thin walled cylinder.
45. Apparatus according to claim 21 or 22 wherein said intermediate transfer member comprises a relatively heat conductive inner layer and a relatively heat insulative outer layer.
- 10 46. Apparatus for transfer of an image from an image bearing surface onto a substrate comprising:  
an intermediate transfer member positioned in operative association with the image bearing surface;  
means for transferring an image from the image bearing  
15 surface onto the intermediate transfer member; and  
means for transferring the image from the intermediate transfer member onto a substrate and wherein said intermediate transfer member comprises a relatively heat conductive inner layer and a relatively heat insulative outer layer.
- 20 47. Apparatus for transfer of multiple images from an image bearing surface onto a substrate comprising:  
an intermediate transfer member positioned in operative

- 37 -

association with the image bearing surface;

means for transferring multiple images from the image bearing surface onto the intermediate transfer member; and

5 means for transferring the multiple images from the intermediate transfer member onto a substrate and wherein said intermediate transfer member comprises a relatively heat conductive inner layer and a relatively heat insulative outer layer.

10 48. Apparatus according to any of claims 21, 22, 33, 34, 46 or 47 wherein said intermediate transfer member has a low effective heat capacity such that the surface temperature of the intermediate transfer member is substantially reduced during transfer of an image therefrom onto a substrate.

15 49. An intermediate transfer member for transfer of an image from an image bearing surface onto a substrate and comprising a thin walled cylinder having a thickness less than 125 microns.

50. Apparatus according to claim 49 and wherein said thin walled cylinder has a thickness less than about 50 microns.

20 51. Apparatus according to claim 50 wherein said thin walled cylinder has a thickness less than about 30 microns.

52. Apparatus according to claim 49 or 51 wherein said thin

- 38 -

walled cylinder comprises a layer of polyester and a thin release layer.

53. Apparatus according to claim 49 or 51 wherein said thin  
walled cylinder comprises a layer of Kapton and a thin release  
5 layer.

54. Apparatus according to claim 51 wherein said thin walled  
cylinder has a thickness less than about 7 microns.

55. Apparatus according to claim 51 wherein said thin walled  
cylinder comprises a metallic material.

10 56. Apparatus according to claim 55 wherein said thin walled  
cylinder comprises a layer of nickel alloy and a thin release  
layer.

57. Apparatus according to claim 51 and also comprising means  
for passing electrical current through said thin walled cylinder  
15 for producing direct resistance heating thereof.

58. Apparatus according to claim 49 wherein said intermediate  
transfer member also comprises means for axially tensioning said  
thin walled cylinder.



59. Apparatus according to claim 49 and wherein said thin walled cylinder is a pneumatically pressurized thin walled cylinder.

60. An intermediate transfer member for transfer of an image from an image bearing surface onto a substrate and comprising a relatively heat conductive inner layer and a relatively heat insulative outer layer.

61. Apparatus according to claim 49 or 60 and wherein said intermediate transfer member has a low effective heat capacity such that the surface temperature of the intermediate transfer member is substantially reduced during transfer of an image therefrom onto a substrate.

62. A method for transfer of an image from an image bearing surface onto a substrate comprising the steps of:

positioning an intermediate transfer member in operative association with the image bearing surface;

transferring an image from the image bearing surface onto the intermediate transfer member; and

transferring the image from the intermediate transfer member onto a substrate and including the steps of heating the intermediate transfer member and the image so as to cause the image to adhere to the substrate and cooling the intermediate transfer member sufficiently such that the adhesion of the image thereto is less than the cohesion of the image.

- 40 -

63. A method for transfer of multiple images from an image bearing surface onto a substrate comprising the steps of:

positioning an intermediate transfer member in operative association with the image bearing surface;

5 transferring multiple images from the image bearing surface onto the intermediate transfer member; and

transferring the multiple images from the intermediate transfer member onto a substrate including the steps of heating the intermediate transfer member and the image so as to cause the  
10 image to adhere to the substrate and cooling the intermediate transfer member sufficiently such that the adhesion of the image thereto is less than the cohesion of the image.

64. A method according to claim 62 or 63 wherein the image is a toner image and wherein said step of transferring the image  
15 from the intermediate transfer member to said substrate is operative to heat the toner image to a temperature below its melting point.

65. A method according to claim 62 or 63 wherein the image is a liquid toner image including particles and wherein said step of  
20 transferring the image from the intermediate transfer member to said substrate is operative to heat the liquid toner image to a temperature below the melting point of said particles.

- 41 -

66. A method according to claim 62 or 63 wherein the image is a liquid image including pigmented particles and wherein said step of transferring the image from the intermediate transfer member to said substrate is operative to heat the liquid image to a temperature below the melting point of said pigmented particles.
67. A method according to claim 64 wherein said step of transferring the image from the intermediate transfer means onto said substrate is operative to heat said image to a temperature at which it solvates.
68. A method according to claim 64 wherein said step of transferring the image from the intermediate transfer means onto said substrate is operative to cool said image to below said solvation temperature.
69. A method according to claim 62 or 63 wherein the image is a toner image and wherein said step of transferring the image from the intermediate transfer member to said substrate is operative to heat the toner image to a temperature above its melting point.
70. A method according to claim 62 or 63 wherein the image is a liquid image including pigmented particles and wherein said step of transferring the image from the intermediate transfer member to said substrate is operative to heat the liquid image to a

- 42 -

temperature above the melting point of said pigmented particles.

71. A method according to claim 69 wherein said step of transferring the image from the intermediate transfer means onto said substrate is operative to cool said image to below said melting point.

72. A method according to claim 62 or 63 wherein said intermediate transfer member comprises a thin walled cylinder and also comprising the step of passing electrical current through said thin walled cylinder for producing direct resistance heating thereof.

73. A method according to claim 62 or 63 wherein said intermediate transfer member comprises a thin walled cylinder and also comprising the step of axially tensioning said thin walled cylinder.

74. A method according to claim 62 or 63 wherein said intermediate transfer member comprises a thin walled cylinder and wherein also comprising the step of pneumatically pressurizing said thin walled cylinder.

75. A method according to claim 62 or 63 wherein said intermediate transfer member has a low effective heat capacity

such that the surface temperature of the intermediate transfer member is substantially reduced during transfer of an image therefrom onto a substrate.

76. Apparatus according to claim 39 wherein said thin walled  
5 cylinder comprises a metallic material.

77. Apparatus according to claim 39 and also comprising means for passing electrical current through said thin walled cylinder for producing direct resistance heating thereof.

78. Apparatus according to claim 54 wherein said thin walled  
10 cylinder comprises a metallic material.

79. A method according to claim 67 wherein said step of transferring the image from the intermediate transfer means onto said substrate is operative to cool said image to below said solvation temperature.

15 80. Apparatus according to claim 1 and wherein development of the image takes place at a first temperature  $T_1$ ; transfer of the image to the intermediate transfer member takes place at an image temperature  $T_2$ , higher than  $T_1$  and final transfer from the intermediate transfer member to the substrate takes place at a  
20 temperature  $T_3$  higher than temperature  $T_2$ .

## AMENDED CLAIMS

[received by the International Bureau  
on 20 February 1990 (20.02.90);  
original claims 23, 28, 64, and 69 cancelled;  
claims 1, 11, 16, 21, 22, 25, 29, 30, 33,  
49, 62, 63, 65, 66, 70 and 71 amended;  
new claims 81-86 added;  
other claims unchanged (14 pages)]

- 1
- 2 1. Apparatus for transfer of a liquid toner image,  
3 comprising carrier liquid and toner particles which solvate  
4 said carrier liquid at a solvation temperature above room  
5 temperature, from an image bearing surface to a substrate,  
6 the apparatus comprising:  
7 an intermediate transfer member arranged in operative  
8 association with said image bearing surface;  
9 first transfer means operative for transferring said  
10 image from said image bearing surface onto said intermediate  
11 transfer member; and  
12 heating means operative for heating said image on said  
13 intermediate transfer member to a temperature above said  
14 solvation temperature, below the melting point of the toner  
15 particles and below the boiling point of said carrier liquid  
16 prior to transfer of the image to said substrate so as to  
17 cause the image to adhere to said substrate.  
18
- 19 2. Apparatus according to claim 1 and comprising second  
20 transfer means operative for transferring said heated image  
21 from said intermediate transfer member to said substrate,  
22 said second transfer means being operative for cooling said  
23 intermediate transfer member sufficiently such that the  
24 adhesion of said image thereto is less than the cohesion of  
25 said image.  
26
- 27 3. Apparatus according to claim 1 wherein said first  
28 transfer means includes means for transferring multiple  
29 images from said image bearing surface onto said  
30 intermediate transfer member.  
31
- 32 4. Apparatus according to claim 1 wherein said toner  
33 particles in said liquid toner image are pigmented.  
34
- 35 5. Apparatus according to claim 1 wherein said heating  
36 means is operative to heat said image such that said image  
37 remains at a temperature above said solvation temperature  
38 until contact of said image with said substrate.

- 1 6. Apparatus according to claim 1 wherein said second  
2 transfer means in conjunction with said substrate is  
3 operative to cool said image sufficiently such that the  
4 adhesion of the image to said intermediate transfer member  
5 is less than the cohesion of said image.  
6
- 7 7. Apparatus according to claim 1 wherein said intermediate  
8 transfer member comprises a thin walled cylinder.  
9
- 10 8. Apparatus according to claim 7 wherein said thin walled  
11 cylinder has a thickness less than 125 microns.  
12
- 13 9. Apparatus according to claim 7 wherein said thin walled  
14 cylinder has a thickness less than about 50 microns.  
15
- 16 10. Apparatus according to claim 7 wherein said thin walled  
17 cylinder has a thickness less than about 30 microns.  
18
- 19 11. Apparatus according to claim 7 wherein said thin  
20 walled cylinder comprises a layer of polymer material and a  
21 thin release layer.  
22
- 23 12. Apparatus according to claim 7 wherein said thin walled  
24 cylinder has a thickness less than about 7 microns.  
25
- 26 13. Apparatus according to claim 7 wherein said thin walled  
27 cylinder comprises a metallic material.  
28
- 29 14. Apparatus according to claim 1 wherein said  
30 intermediate transfer member comprises a relatively heat  
31 conductive inner layer and a relatively heat insulative  
32 outer layer.  
33
- 34 15. Apparatus according to claim 1 and wherein said  
35 intermediate transfer member has a low effective heat  
36 capacity such that the surface temperature of said  
37 intermediate transfer member is substantially reduced during  
38 transfer of said image therefrom onto said substrate.

- 1 16. A method for transfer of a liquid toner image,  
2 comprising carrier liquid and toner particles which solvate  
3 said carrier liquid at a solvation temperature above room  
4 temperature, from an image bearing surface to a substrate,  
5 comprising the steps of:  
6 transferring said image from said image bearing surface  
7 onto an intermediate transfer member; and  
8 heating said image on said intermediate transfer member  
9 to a temperature above said solvation temperature, below the  
10 melting point of the toner particles and below the boiling  
11 point of said carrier liquid prior to transfer of said  
12 image to said substrate so as to cause said image to adhere  
13 to said substrate.  
14
- 15 17. The method of claim 16 and including the step of  
16 cooling said intermediate transfer member sufficiently such  
17 that the adhesion of said image thereto is less than the  
18 cohesion of the image.  
19
- 20 18. The method of claim 16 and including the step of  
21 cooling said image sufficiently such that the adhesion of  
22 said image to said intermediate transfer member is less than  
23 the cohesion of said image.  
24
- 25 19. The method of claim 16 and wherein the step of  
26 transferring said image from said image bearing surface is  
27 repeated a plurality of times, each transfer corresponding  
28 to an image of a different color.  
29
- 30 20. A method according to claim 16 and including the step  
31 of transferring said heated image from said intermediate  
32 transfer member to said substrate, wherein said step of  
33 transferring the image from the intermediate transfer member  
34 onto said substrate is operative to cool said image to below  
35 said solvation temperature.  
36
- 37 21. Apparatus for transfer of an liquid image from an  
38 image bearing surface onto a substrate comprising:



- 1           an intermediate transfer member positioned in  
2 operative association with the image bearing surface;  
3           apparatus for providing a liquid image on said  
4 image bearing surface;  
5           means for transferring said liquid image from the  
6 image bearing surface onto the intermediate transfer member;  
7 and  
8           means for transferring the liquid image from the  
9 intermediate transfer member onto a substrate and being  
10 operative for heating the intermediate transfer member and  
11 the liquid image so as to cause the image to adhere to the  
12 substrate and for cooling the intermediate transfer member  
13 sufficiently such that the adhesion of the image thereto is  
14 less than the cohesion of the image.  
15
- 16 22. Apparatus for transfer of multiple liquid images from  
17 an image bearing surface onto a substrate comprising:  
18           an intermediate transfer member positioned in  
19 operative association with the image bearing surface;  
20           apparatus for providing liquid images on said  
21 image bearing surface;  
22           means for transferring said multiple liquid images  
23 from the image bearing surface onto the intermediate  
24 transfer member; and  
25           means for transferring the multiple liquid images  
26 from the intermediate transfer member onto a substrate and  
27 being operative for heating the intermediate transfer member  
28 and the liquid image so as to cause the image to adhere to  
29 the substrate and for cooling the intermediate transfer  
30 member sufficiently such that the adhesion of the image  
31 thereto is less than the cohesion of the image.  
32
- 33 23. (Canceled)  
34
- 35 24. Apparatus according to claim 21 or 22 wherein the  
36 image is a liquid toner image including particles and  
37 wherein said means for transferring the image from the  
38 intermediate transfer member to said substrate is operative

1 to heat the liquid toner image to a temperature below the  
2 melting point of said particles.

3

4 25. Apparatus according to claim 21 or 22 wherein the  
5 liquid image includes pigmented particles and wherein said  
6 means for transferring the image from the intermediate  
7 transfer member to said substrate is operative to heat the  
8 liquid image to a temperature below the melting point of  
9 said pigmented particles.

10

11 26. Apparatus according to claim 21 or 22 wherein said  
12 means for transferring the image from the intermediate  
13 transfer means onto said substrate is operative to heat said  
14 image to a temperature at which it solvates.

15

16 27. Apparatus according to claim 26 wherein said means for  
17 transferring the image from the intermediate transfer means  
18 onto said substrate is operative to cool said image to below  
19 said solvation temperature.

20

21 28. (Canceled)

22

23 29. Apparatus according to claim 21 or 22 wherein the  
24 liquid image includes pigmented particles and wherein said  
25 means for transferring the image from the intermediate  
26 transfer member to said substrate is operative to heat the  
27 liquid image to a temperature above the melting point of  
28 said pigmented particles.

29

30 30. Apparatus according to claim 29 wherein said means for  
31 transferring the image from the intermediate transfer means  
32 onto said substrate is operative to cool said image to below  
33 said melting point.

34

35 31. Apparatus according to claim 21 or 22 wherein said  
36 intermediate transfer member comprises a thin walled  
37 cylinder.

38

- 1 32. Apparatus according to claim 31 wherein said thin  
2 walled cylinder has a thickness less than 125 microns.  
3
- 4 33. Apparatus for transfer of an image from an image  
5 bearing surface onto a substrate comprising:  
6 an intermediate transfer member positioned in  
7 operative association with the image bearing surface;  
8 means for transferring an image from the image  
9 bearing surface onto the intermediate transfer member; and  
10 means for transferring the image from the  
11 intermediate transfer member onto a substrate and wherein  
12 said intermediate transfer member comprises a thin walled  
13 cylinder having end portions and a cylindrical image surface  
14 therebetween and wherein said thin walled cylinder has a  
15 thickness of less than 125 microns which is unbacked by a  
16 solid structural support between said end portions.  
17
- 18 34. Apparatus for transfer of multiple images from an image  
19 bearing surface onto a substrate comprising:  
20 an intermediate transfer member positioned in  
21 operative association with the image bearing surface;  
22 means for transferring multiple images from the  
23 image bearing surface onto the intermediate transfer member;  
24 and  
25 means for transferring the multiple images from  
26 the intermediate transfer member onto a substrate and  
27 wherein said intermediate transfer member comprises a thin  
28 walled cylinder having end portions and a cylindrical image  
29 surface therebetween and wherein said thin walled cylinder  
30 has a thickness of less than 125 microns which is unbacked  
31 by a solid structural support between said end portions.  
32
- 33 35. Apparatus according to claim 32, 33 or 34 wherein said  
34 thin walled cylinder has a thickness less than about 50  
35 microns.  
36
- 37 36. Apparatus according to claim 35 wherein said thin  
38 walled cylinder has a thickness less than about 30 microns.

- 1 37. Apparatus according to any of claims 32, 33 or 34  
2 wherein said thin walled cylinder comprises a layer of  
3 polyester and a thin release layer.  
4
- 5 38. Apparatus according to any of claims 32, 33 or 34  
6 wherein said thin walled cylinder comprises a layer of  
7 Kapton and a thin release layer.  
8
- 9 39. Apparatus according to claim 36 wherein said thin  
10 walled cylinder has a thickness less than about 7 microns.  
11
- 12 40. Apparatus according to claim 36 wherein said thin  
13 walled cylinder comprises a metallic material.  
14
- 15 41. Apparatus according to claim 40 wherein said thin  
16 walled cylinder comprises a layer of nickel alloy and a thin  
17 release layer.  
18
- 19 42. Apparatus according to claim 36 and also comprising  
20 means for passing electrical current through said thin  
21 walled cylinder for producing direct resistance heating  
22 thereof.  
23
- 24 43. Apparatus according to claim 35 wherein said  
25 intermediate transfer member also comprises means for  
26 axially tensioning said thin walled cylinder.  
27
- 28 44. Apparatus according to claim 35 wherein said thin  
29 walled cylinder is a pneumatically pressurized thin walled  
30 cylinder.  
31
- 32 45. Apparatus according to claim 21 or 22 wherein said  
33 intermediate transfer member comprises a relatively heat  
34 conductive inner layer and a relatively heat insulative  
35 outer layer.  
36
- 37 46. Apparatus for transfer of an image from an image  
38 bearing surface onto a substrate comprising:

- 1           an intermediate transfer member positioned in  
2   operative association with the image bearing surface;  
3           means for transferring an image from the image  
4   bearing surface onto the intermediate transfer member; and  
5           means for transferring the image from the  
6   intermediate transfer member onto a substrate and wherein  
7   said intermediate transfer member comprises a relatively  
8   heat conductive inner layer and a relatively heat insulative  
9   outer layer.
- 10
- 11   47. Apparatus for transfer of multiple images from an image  
12   bearing surface onto a substrate comprising:  
13           an intermediate transfer member positioned in  
14   operative association with the image bearing surface;  
15           means for transferring multiple images from the  
16   image bearing surface onto the intermediate transfer member;  
17   and  
18           means for transferring the multiple images from  
19   the intermediate transfer member onto a substrate and  
20   wherein said intermediate transfer member comprises a  
21   relatively heat conductive inner layer and a relatively heat  
22   insulative outer layer.
- 23
- 24   48. Apparatus according to any of claims 21, 22, 33, 34, 46  
25   or 47 wherein said intermediate transfer member has a low  
26   effective heat capacity such that the surface temperature of  
27   the intermediate transfer member is substantially reduced  
28   during transfer of an image therefrom onto a substrate.
- 29
- 30   49. An intermediate transfer member for transfer of an  
31   image from an image bearing surface onto a substrate and  
32   comprising a thin walled cylinder having end portions and a  
33   cylindrical image surface therebetween and wherein said thin  
34   walled cylinder has a thickness of less than 125 microns  
35   which is unbacked by a solid structural support between said  
36   end portions.
- 37
- 38   50. Apparatus according to claim 49 and wherein said thin

- 1   walled cylinder has a thickness less than about 50 microns.  
2
- 3   51.   Apparatus according to claim 50 wherein said thin  
4   walled cylinder has a thickness less than about 30 microns.  
5
- 6   52.   Apparatus according to claim 49 or 51 wherein said thin  
7   walled cylinder comprises a layer of polyester and a thin  
8   release layer.  
9
- 10   53.   Apparatus according to claim 49 or 51 wherein said  
11   thin walled cylinder comprises a layer of Kapton and a thin  
12   release layer.  
13
- 14   54.   Apparatus according to claim 51 wherein said thin  
15   walled cylinder has a thickness less than about 7 microns.  
16
- 17   55.   Apparatus according to claim 51 wherein said thin  
18   walled cylinder comprises a metallic material.  
19
- 20   56.   Apparatus according to claim 55 wherein said thin  
21   walled cylinder comprises a layer of nickel alloy and a thin  
22   release layer.  
23
- 24   57.   Apparatus according to claim 51 and also comprising  
25   means for passing electrical current through said thin  
26   walled cylinder for producing direct resistance heating  
27   thereof.  
28
- 29   58.   Apparatus according to claim 49 wherein said  
30   intermediate transfer member also comprises means for  
31   axially tensioning said thin walled cylinder.  
32
- 33   59.   Apparatus according to claim 49 and wherein said thin  
34   walled cylinder is a pneumatically pressurized thin walled  
35   cylinder.  
36
- 37   60.   An intermediate transfer member for transfer of an  
38   image from an image bearing surface onto a substrate and

1 comprising a relatively heat conductive inner layer and a  
2 relatively heat insulative outer layer.  
3

4 61. Apparatus according to claim 49 or 60 and wherein said  
5 intermediate transfer member has a low effective heat  
6 capacity such that the surface temperature of the  
7 intermediate transfer member is substantially reduced during  
8 transfer of an image therefrom onto a substrate.  
9

10 62. A method for transfer of a liquid image from an  
11 image bearing surface onto a substrate comprising the steps  
12 of:

13 providing a liquid image on said image bearing  
14 surface;

15 positioning an intermediate transfer member in  
16 operative association with the image bearing surface;

17 transferring said liquid image from the image  
18 bearing surface onto the intermediate transfer member; and

19 transferring the liquid image from the  
20 intermediate transfer member onto a substrate and including  
21 the steps of heating the intermediate transfer member and  
22 the image so as to cause the image to adhere to the  
23 substrate and cooling the intermediate transfer member  
24 sufficiently such that the adhesion of the image thereto is  
25 less than the cohesion of the image.  
26

27 63. A method for transfer of multiple liquid images from  
28 an image bearing surface onto a substrate comprising the  
29 steps of:

30 providing multiple liquid images on said image bearing  
31 surface;

32 positioning an intermediate transfer member in  
33 operative association with the image bearing surface;

34 transferring the multiple liquid images from the  
35 image bearing surface onto the intermediate transfer member;  
36 and

37 transferring the multiple liquid images from the  
38 intermediate transfer member onto a substrate including the

1 steps of heating the intermediate transfer member and the  
2 image so as to cause the image to adhere to the substrate  
3 and cooling the intermediate transfer member sufficiently  
4 such that the adhesion of the image thereto is less than the  
5 cohesion of the image.

6

7 64. (Canceled)

8

9 65. A method according to claim 62 or 63 wherein the  
10 liquid image is a liquid toner image including particles and  
11 wherein said step of transferring the image from the  
12 intermediate transfer member to said substrate is operative  
13 to heat the liquid toner image to a temperature below the  
14 melting point of said particles.

15

16 66. A method according to claim 62 or 63 wherein the image  
17 is a liquid image including pigmented particles and wherein  
18 said step of transferring the image from the intermediate  
19 transfer member to said substrate is operative to heat the  
20 liquid image to a temperature below the melting point of  
21 said pigmented particles.

22

23 67. A method according to claim 64 wherein said step of  
24 transferring the image from the intermediate transfer means  
25 onto said substrate is operative to heat said image to a  
26 temperature at which it solvates.

27

28 68. A method according to claim 64 wherein said step of  
29 transferring the image from the intermediate transfer means  
30 onto said substrate is operative to cool said image to below  
31 said solvation temperature.

32

33 69. (Canceled)

34

35 70. A method according to claim 62 or 63 wherein the  
36 liquid image includes pigmented particles and wherein said  
37 step of transferring the image from the intermediate  
38 transfer member to said substrate is operative to heat the



1 liquid image to a temperature above the melting point of  
2 said pigmented particles.

3

4 71. A method according to claim 70 wherein said step of  
5 transferring the image from the intermediate transfer means  
6 onto said substrate is operative to cool said image to below  
7 said melting point.

8

9 72. A method according to claim 62 or 63 wherein said  
10 intermediate transfer member comprises a thin walled  
11 cylinder and also comprising the step of passing electrical  
12 current through said thin walled cylinder for producing  
13 direct resistance heating thereof.

14

15 73. A method according to claim 62 or 63 wherein said  
16 intermediate transfer member comprises a thin walled  
17 cylinder and also comprising the step of axially tensioning  
18 said thin walled cylinder.

19

20 74. A method according to claim 62 or 63 wherein said  
21 intermediate transfer member comprises a thin walled  
22 cylinder and wherein also comprising the step of  
23 pneumatically pressurizing said thin walled cylinder.

24

25 75. A method according to claim 62 or 63 wherein said  
26 intermediate transfer member has a low effective heat  
27 capacity such that the surface temperature of the  
28 intermediate transfer member is substantially reduced during  
29 transfer of an image therefrom onto a substrate.

30

31 76. Apparatus according to claim 39 wherein said thin  
32 walled cylinder comprises a metallic material.

33

34 77. Apparatus according to claim 39 and also comprising  
35 means for passing electrical current through said thin  
36 walled cylinder for producing direct resistance heating  
37 thereof.

38

1 78. Apparatus according to claim 54 wherein said thin  
2 walled cylinder comprises a metallic material.

3

4 79. A method according to claim 67 wherein said step of  
5 transferring the image from the intermediate transfer means  
6 onto said substrate is operative to cool said image to below  
7 said solvation temperature.

8

9 80. Apparatus according to claim 1 and wherein  
10 development of the image takes place at a first temperature  
11  $T_1$ ; transfer of the image to the intermediate transfer  
12 member takes place at an image temperature  $T_2$ , higher than  
13  $T_1$  and final transfer from the intermediate transfer member  
14 to the substrate takes place at a temperature  $T_3$  higher  
15 than temperature  $T_2$ .

16

17 81. An imaging apparatus for printing an image from a  
18 latent image formed on a latent image bearing surface  
19 comprising:

20 developing means for developing said latent image with  
21 a liquid developer, comprising carrier liquid and charged  
22 pigmented particles, to form a developed image;

23 an intermediate transfer member for receiving said  
24 developed image from said latent image bearing surface for  
25 subsequent transfer to a final substrate; and

26 heating means for heating said developed image during  
27 its transfer from said latent image bearing surface to said  
28 intermediate transfer member.

29

30 82. Imaging apparatus according to claim 81 further  
31 comprising:

32 means for further heating said image prior to said  
33 subsequent transfer to said final substrate.

34

35 83. A method for forming an image on a final substrate  
36 from a latent image on an image forming surface comprising  
37 the steps of:

38 developing said latent image using a liquid developer

1 comprising carrier liquid and charged particles to form a  
2 liquid toner image at a first temperature; and  
3 transferring said liquid toner image to an intermediate  
4 transfer member, said liquid toner image being at a higher  
5 temperature during said transfer step than said first  
6 temperature.

7  
8 84. A method according to claim 83 further comprising the  
9 step of:

10 further transferring said liquid toner image from said  
11 intermediate transfer member to a final substrate, said  
12 liquid toner image being at a higher temperature during said  
13 further transferring step than during said transferring  
14 step.


15  
16 85. A method according to claim 84 wherein said transfer  
17 is by electrophoresis.




18  
19 86. An imaging apparatus for printing an image from a  
20 latent image formed on a latent image bearing surface  
21 comprising:


22 developing means for developing said latent image with  
23 a liquid developer, comprising carrier liquid and charged  
24 pigmented particles, to form a developed image;

25 a heated intermediate transfer member for receiving  
26 said developed image from said latent image bearing surface  
27 for subsequent transfer to a final substrate; and

28 cooling means for cooling a portion of said  
29 intermediate transfer member prior to transfer of a portion  
30 of said developed image to said cooled portion said  
31 intermediate transfer member.

FIG. 1








FIG. 4A




FIG. 5A




FIG. 4B








FIG. 5B









FIG. 9



# INTERNATIONAL SEARCH REPORT

International Application No PCT/NL 89/00073

**I. CLASSIFICATION OF SUBJECT MATTER** (if several classification symbols apply, indicate all) \*  
According to International Patent Classification (IPC) or to both National Classification and IPC  
IPC5: G 03 G 15/16

## II. FIELDS SEARCHED

Classification System	Minimum Documentation Searched ?	Classification Symbols
IPC5		G 03 G

Documentation Searched other than Minimum Documentation  
to the extent that such Documents are included in the Fields Searched \*

## III. DOCUMENTS CONSIDERED TO BE RELEVANT \*

Category *	Citation of Document, <sup>11</sup> with indication, where appropriate, of the relevant passages <sup>12</sup>	Relevant to Claim No. <sup>13</sup>
A	DE, C2, 3211905 (CANON K.K.) 9 May 1985, see figure 1; claim 1 --	16, 19, 20, 22 34, 47, 63
A	US, A, 3838919 (TORU TAKAHASHI) 1 October 1974, see figure 2; claim 1 --	16, 19, 20, 22 34, 47, 63
X	US, A, 4015027 (WILLIAM R. BUCHAN ET AL) 29 March 1977, see figures 2,5-7 --	1, 2, 4-6, 14, 16-18, 21-30, 46, 62, 64-71
X	US, A, 4430412 (TADASHI MIWA ET AL) 7 February 1984, see figures 2-3; claim 1 --	1, 2, 4-6, 14, 16-18, 21-30, 46, 62, 64-71

\* Special categories of cited documents: <sup>14</sup>

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubt on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

## IV. CERTIFICATION

Date of the Actual Completion of the International Search  
21st December 1989

Date of Mailing of this International Search Report

10.01.90

International Searching Authority

EUROPEAN PATENT OFFICE

Signature of Authorized Officer

T.K. WILLIS

III. DOCUMENTS CONSIDERED TO BE RELEVANT (CONTINUED FROM THE SECOND SHEET)		
Category *	Citation of Document, with indication, where appropriate, of the relevant passages	Relevant to Claim No
X	US, A, 4531825 (TADASHI MIWA ET AL) 30 July 1985, see figures 6,7 details 5a,b,c --	1, 2, 4-6, 14, 16-18, 21-30, 46, 62, 64-71
X	US, A, 4645327 (KIYOSHI KIMURA ET AL) 24 February 1987, see figures, details 1,17 --	1, 2, 4-6, 14, 16-18, 21-30, 46, 62, 64-71
X	Patent Abstracts of Japan, Vol 11, No 358, P639, abstract of JP 62-134671, publ 1987-06-17 CANON INC, see details 2, 9, 10 -----	1, 2, 4-6, 16- 18, 21-30, 46, 62, 64-71

**ANNEX TO THE INTERNATIONAL SEARCH REPORT  
ON INTERNATIONAL PATENT APPLICATION NO. PCT/NL 89/00073**

SA 31587

This annex lists the patent family members relating to the patent documents cited in the above-mentioned international search report.  
The members are as contained in the European Patent Office (EPO) file on 08/11/89  
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
DE-C2- 3211905	09/05/85	JP-A- 59104672	16/06/84
US-A- 3838919	01/10/74	US-A- 3904406	09/09/75
US-A- 4015027	29/03/77	US-A- 3893761	08/07/75
		US-A- 3993825	23/11/76
US-A- 4430412	07/02/84	DE-A- 3241816	26/05/83
		JP-A- 58083876	19/05/83
		JP-A- 58085463	21/05/83
		JP-A- 58085464	21/05/83
US-A- 4531825	30/07/85	JP-A- 58090645	30/05/83
		DE-A- 3242797	01/06/83
		JP-A- 58090654	30/05/83
		JP-A- 58090655	30/05/83
US-A- 4645327	24/02/87	JP-A- 59154460	03/09/84
		JP-A- 59162578	13/09/84

EPO FORM P001

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82